



NTN BEARING CORP.OF America LTD.

1.575 Inch | 40 Millimeter x 1.937 Inch | 49.2 Millimeter x 1.937 Inch | 49.2 Millimeter NTN ucp208 Bearing



Bearing No. ucp208

ucp208 Bearing 2D drawings and 3D CAD models

Category	Pillow Block Bearings
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight	2.174
EAN	4547359224917
Product Group	M06110
Number of Mounting Holes	2
Mounting Method	Set Screw
Housing Style	2 Bolt Pillow Block
Rolling Element	Ball Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-expansion
Mounting Bolts	14 Millimeter
Relubricatable	No
Insert Part Number	UC208
Seals	Single Lip Land Riding
Housing Configuration	1 Piece Solid
Inch - Metric	Metric
Other Features	Single Row Light Duty Wide Inner Race Has Flinger
Long Description	2 Bolt Pillow Block; 40MM Bore; 49.2MM Base to Center Height; Set Screw Mount; Ball Bearing; No



NTN BEARING CORP.OF America LTD.

	Relubricatable; Cast Iron; Single Lip Land Riding; Non-expansion
Category	Pillow Block
UNSPSC	31171511
Harmonized Tariff Code	8483.20.40.40
Noun	Bearing
Keyword String	Pillow Block
Manufacturer URL	http://www.ntnamerica.com
Manufacturer Item Number	UCP208
Weight / LBS	4.189
D	1.937 Inch 49.2 Millimeter
Actual Bolt Center to Center	5.4 Inch 136 Millimeter
Bolt Spacing Minimum	0 Inch 0 Millimeter
Nominal Bolt Center to Center	5.4 Inch 136 Millimeter
d	1.575 Inch 40 Millimeter
B	1.937 Inch 49.2 Millimeter
Bolt Spacing Maximum	0 Inch 0 Millimeter
mounting:	Two-Bolt Base
finish/coating:	Uncoated
bore diameter:	40 mm
overall width:	1-15/16 in
bore type:	Round
radial dynamic load capacity:	6550 lb
base to bore centerline:	1.9370 in
radial static load capacity:	4000 lb
duty type:	Light Duty
base width:	54 mm
housing material:	Cast Iron
bolt center-to-center length:	137 mm



NTN BEARING CORP.OF America LTD.

locking device:	Set Screw
lubrication type:	Lubrication Fitting
seal type:	Contact with Flinger
series:	UCP2
expansion type:	Non-Expansion Bearing (Fixed)
replacement bearing:	UC208D1
overall length:	184 mm
standards met:	ANSI, ISO, AFBMA
overall height:	98 mm